



# Telescopic – vertical outlet

## Product information for the product group

### ACO Product benefits

- Fully inspectable and cleanable
- Fully removable and easily cleanable stainless steel foul air trap (FAT)
- Full drainability
- Internal radii equal or larger than 3 mm
- Fully welded hygienic joints
- Steel thickness min. 1,5 mm
- Fully pickled and passivated





- BIM models are available in ACO Building Drainage BIM Revit libraries
- Certified according to EN 1253-1
- Hygienic design following EN 1672, EN ISO 14159 and EHEDG document 8, 13 and 44
- Available in 1.4301 (304) or 1.4404 (316L) grades of stainless steel
- Suitable for all floor types including vinyl flooring
- Location flange or integrated membrane flange for either adhesive bonding or mechanical clamp
- Telescopic friction ring included
- Certified fire protective solution available for classes EI 90 – EI 180 (EN 13 501-2)












## Item Technical Data 408151

Flange design	Outlet diameter Ø [mm]	Flow rate		Odour trap	Material
		Min. flow rate [l/s]	Max. flow rate [l/s]		
Adhesive bonding flange	75	2.7	3.3	With	1.4404

## Accessories

	Description	Used with	Item number
	<b>ACO Easy FAT</b> <b>Features and Benefits:</b> <ul style="list-style-type: none"> <li>■ Fully removable and easily cleanable</li> <li>■ Steel thickness min. 1,2 mm</li> <li>■ Fully pickled and passivated</li> <li>■ Fully tested and classified according to EN 1253-1</li> </ul> <b>Attributes:</b> <ul style="list-style-type: none"> <li>■ Without silt basket</li> <li>■ Flow rate with horizontal gully: 2,15 l/s</li> <li>■ Flow rate with vertical gully: 2,6 l/s</li> </ul>	<ul style="list-style-type: none"> <li>■ ACO gully 157 telescopic</li> <li>■ ACO box channels with outlet øD 142 mm and outer width above and including 300 mm</li> <li>■ ACO modular box channel 200 - outlet øD 142 mm</li> <li>■ ACO modular slot channel 20 - outlet øD 142 mm</li> </ul>	
	Material grade 1.4301 (304)		448810
	Material grade 1.4404 (316L)		448811
	<b>ACO Easy FAT</b> <b>Features and Benefits:</b> <ul style="list-style-type: none"> <li>■ Simplified and separate handling with FAT and silt basket</li> <li>■ Fully removable and easily cleanable</li> <li>■ Steel thickness min. 1,2 mm</li> <li>■ Fully pickled and passivated</li> <li>■ Fully tested and classified according to EN 1253-1</li> </ul> <b>Attributes:</b> <ul style="list-style-type: none"> <li>■ With silt basket</li> <li>■ Flow rate with horizontal gully: 2,1 l/s</li> <li>■ Flow rate with vertical gully: 2,4 l/s</li> </ul>	<ul style="list-style-type: none"> <li>■ ACO gully 157 telescopic</li> <li>■ ACO box channels with outlet øD 142 mm and outer width above and including 300 mm</li> <li>■ ACO modular box channel 200 - outlet øD 142 mm</li> <li>■ ACO modular slot channel 20 - outlet øD 142 mm</li> </ul>	
	Material grade 1.4301 (304)		449096
	Material grade 1.4404 (316L)		449128
	<b>Silt basket</b> <ul style="list-style-type: none"> <li>■ Stainless steel</li> <li>■ 0,6 litre capacity</li> </ul>	<ul style="list-style-type: none"> <li>■ ACO gully 157 - vertical <ul style="list-style-type: none"> <li><input type="checkbox"/> Fixed height or telescopic</li> </ul> </li> <li>■ ACO hygienic box channel <ul style="list-style-type: none"> <li><input type="checkbox"/> Channel dimension</li> <li><input type="checkbox"/> Width Wo [mm]: 300, 400, 500, 600, 800</li> <li><input type="checkbox"/> Outlet øD [mm]: 142 or welded with ACO hygienic gully 157</li> <li><input type="checkbox"/> Direction of gully outlet: vertical</li> </ul> </li> </ul>	
	Material grade 1.4301 (304)		416904
	Material grade 1.4404 (316L)		416905
	<b>Silt basket</b> <ul style="list-style-type: none"> <li>■ Stainless steel</li> <li>■ 0,3 litre capacity</li> </ul>	<ul style="list-style-type: none"> <li>■ ACO gully 142 and 157 - horizontal <ul style="list-style-type: none"> <li><input type="checkbox"/> Fixed height or Telescopic</li> </ul> </li> <li>■ ACO hygienic box channel <ul style="list-style-type: none"> <li><input type="checkbox"/> Channel dimension</li> <li><input type="checkbox"/> Width Wo [mm]: 300, 400, 500, 600, 800</li> <li><input type="checkbox"/> Outlet øD [mm]: 142 or welded with ACO hygienic gully 157</li> <li><input type="checkbox"/> Direction of gully outlet: horizontal</li> </ul> </li> </ul>	
	Material grade 1.4301 (304)		416906
	Material grade 1.4404 (316L)		416907

	Description	Used with	Item number
	<b>ACO tundish</b> ■ Stainless steel ■ Material grade 1.4301 (304)	■ ACO gully top size 200 x 200 mm	415918
	<b>ACO tundish</b> ■ Stainless steel ■ Material grade 1.4301 (304)	■ ACO gully top size 250 x 250 mm	413546
	<b>ACO tundish portable</b> ■ Stainless steel ■ Material grade 1.4301 (304)	■ ACO drainage independent of visible edge dimensions	415821
	■ Fixed height, vertical ■ Telescopic, vertical ■ Made from 1.4404 (316) grade of stainless steel ■ NBR	■ ACO hygienic gully 157 <input type="checkbox"/> Fixed height, vertical <input type="checkbox"/> Telescopic, vertical	
	<b>ACO fire resistant kit for gully 157/DN 75</b>		416932
	<b>ACO fire resistant kit for gully 157/DN 110</b>		416933
	<b>Odour trap</b> Stainless steel ■ Height 50 mm	■ ACO hygienic gully 157 <input type="checkbox"/> Telescopic	
	Material grade 1.4301 (304)		408200
  	Material grade 1.4404 (316L)		408210
	<b>Standard foul air trap support</b> NBR	■ ACO hygienic gully 157 <input type="checkbox"/> Fixed height <input type="checkbox"/> Telescopic	408201
	<b>Friction ring</b> SBR	■ ACO hygienic gully 157 <input type="checkbox"/> Telescopic	408205

You can find further accessories under → <https://www.buildingdrainage.aco/search/?q=408151>