


Channel body ACO ShowerDrain C, Installation height top edge screed: 57 – 128 mm (200 mm)

Product information for the product group


ACO Product benefits

- Minimum installation height
- Meets requirements of all sound protection levels (SSt I-III in acc. with VDI 4100)
- Free access to the pipe for optimal cleaning
- Factory-welded hydro-shaped gully, guarantees permanent tightness
- Removable foul air trap for optimal cleaning
- High drainage capacity



- Material: Stainless steel, material grade 304
- Load class: K3
- Internal channel width: 64 mm
- Installation height: 69-140 mm (incl. 12 mm frame height)
- Flow rate:
 - 0.56 l/s (WS25 with 10 mm build-up)
 - 0.62 l/s (WS25 with 20 mm build-up as per EN 1253-1)
- Outlet socket: Suitable for all push-fit pipe socket systems
- Socket versions:
 - Socket horizontal/central: ND 50
 - Socket horizontal/lateral: ND 40
 - Socket horizontal: ND 50
- Foul air trap: 2-part, removable
- Type of flange: surrounding flange with sealing membrane, surrounding flange, wall flange or without flange
- Channel body: Pickle passivated
- Mounting: Ready for installation
- Sound protection (as standard)
- Height adjustability: 48 respectively 74 mm using height-adjustable feet (to be ordered as an accessory)
- Grating variants: Stainless steel design gratings, tileable cover
- Supplementary components: ACO ShowerStep and ACO EasyStop

Item Technical Data 9010.85.50

	Description	Odour trap	Dimensions		
			L1	L2	B
			[mm]	[mm]	[mm]
	Wall flange with sealing membrane, socket horizontal/central	With	685	745	122

